

OPTICAL SMOKE DETECTOR

Part Number 5310

Dimensions	ø102mm x 48mm (Including Base)
Type	Conventional
Wire Gauge	0.4mm - 2.0mm TWIN
Weight (Including base)	160g
Test Facility	Simulated Smoke
Relay	30V/0.5A
Operating Voltage	9 - 30VDC
Standby Current @ 12v	< 50µA
Alarm Current @ 12v	29mA
Ingress Protection	IP30
Relative Humidity Resistance	(93±3)% @ 40˚C
Operating Temperature	-10°C to 60°C



www.osukl.com | sales@osukl.com | +44 (0)1425 610022

Oceanic Systems (UK) Ltd

Unit 10-11 Milton Business Centre, Wick Drive, New Milton, Hampshire, BH25 6RH, United Kingdom

Tel: +44(0)1425610022
Email: sales@osukl.com
Web: www.osukl.com

Copyright © 2020 Oceanic Systems (UK) Ltd. All rights reserved.

Our policy is one of continuous product improvement so product specifications are subject to change without notice. Oceanic Systems products are designed to be accurate and reliable. However, they should be used only as aids to vessel monitoring, and not as a replacement for traditional navigation and vessel monitoring techniques.

NMEA2000® is a registered trademark of the National Marine Electronics Association.